




## SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** Animal ID Tag Cement (RCB-572)  
**Other means of identification:** Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**  
 Relevant uses: Adhesive. For professional users/industrial user only.  
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
**Manufacturer:**  
 The Ruscoe Company  
 485 Kenmore Blvd  
 44301 Akron - United States Phone: 330-253-8148  
[Sales@Ruscoe.com](mailto:Sales@Ruscoe.com); [SDS@Ruscoe.com](mailto:SDS@Ruscoe.com)  
[www.ruscoe.com](http://www.ruscoe.com)
- Supplier**  
 BEACON AUTOMATION PTY LTD  
 30 Glen Munro Road  
 MUSWELLBROOK, NSW 2333, AUSTRALIA  
 Ph +61 2 6541 2345 [www.beaconhd.com.au](http://www.beaconhd.com.au)  
 NZ Free phone 0800 22 33 99
- 1.4 Emergency phone numbers:**  
 National Poison Centre. New Zealand: 0800 764 766 (0800 POISON) 24 hours  
 Chemtrec 1-800-424-9300

## SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
 29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Asp. Tox. 1: Aspiration hazard, Category 1, H304  
 Flam. Liq. 2: Flammable liquids, Category 2, H225  
 Repr. 2: Reproductive toxicity, Category 2, H361  
 Skin Irrit. 2: Skin irritation, Category 2, H315  
 Skin Sens. 1: Sensitisation, skin, Category 1, H317  
 STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373  
 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
**Danger**



### Hazard statements:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
 Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
 Skin Irrit. 2: H315 - Causes skin irritation.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
 STOT SE 3: H336 - May cause drowsiness or dizziness.

### Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P308+P313: IF exposed or concerned: Get medical advice/attention.  
 P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
 P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.



## SECTION 2: HAZARD(S) IDENTIFICATION

### Substances that contribute to the classification

HEXANE (CAS: 110-54-3); COLOPHONIUM (CAS: 8050-09-7)

### Additional labelling



### WARNING

This product can expose you to chemicals including n-hexane, Toluene, Benzene, which is [are] known to the State of California to cause cancer, and Benzene, Ethylbenzene, Naphthalene, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### 2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances:

Non-applicable

### 3.2 Mixtures:

**Chemical description:** Mixture composed of additives and resins in solvents

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 110-54-3	<b>n-hexane</b> Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	<b>25 - &lt;50 %</b>
CAS: 8050-09-7	<b>Rosin</b> Skin Sens. 1: H317 - Warning	<b>1 - &lt;2.5 %</b>

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST-AID MEASURES

### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

### 4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.



- 4.3 Indication of immediate medical attention and special treatment needed, if necessary:**  
Not available

## SECTION 5: FIRE-FIGHTING MEASURES

- 5.1 Suitable (and unsuitable) extinguishing media: Suitable extinguishing media:**  
Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)
- Unsuitable extinguishing media:**  
Water jet
- 5.2 Specific hazards arising from the chemical:**  
As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.
- 5.3 Special protective equipment and precautions for fire-fighters:**  
Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)
- Additional provisions:**  
As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:**  
**For non-emergency personnel:**  
Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form and also ensuring that all surfaces are connected to the ground.
- For emergency responders:**  
Wear protective equipment. Keep unprotected persons away. See section 8.
- 6.2 Environmental precautions:**  
This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.
- 6.3 Methods and materials for containment and cleaning up:**  
For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802. Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.
- 6.4 Reference to other sections:**  
See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling:**
- A. General precautions for safe use  
Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container.  
Maintain order and cleanliness where dangerous products are used.
  - B. Technical recommendations for the prevention of fires and explosions  
Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.
  - C. Technical recommendations on general occupational hygiene  
PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply



## SECTION 7: HANDLING AND STORAGE

with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D. Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A. Specific storage requirements

Minimum Temp.: 5 °C (41 °F)

Maximum Temp.: 32 °C (90 °F)

B. General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	500 ppm	1800 mg/m <sup>3</sup>
n-hexane	Ceiling Values - TWA PEL		
CAS: 110-54-3	8-hour TWA PEL	300 ppm	1050 mg/m <sup>3</sup>
cyclohexane	Ceiling Values - TWA PEL		
CAS: 110-82-7	8-hour TWA PEL	200 ppm	300 mg/m <sup>3</sup>
Toluene <sup>(1)</sup>	Ceiling Values - TWA PEL		
CAS: 108-88-3	8-hour TWA PEL	10 ppm	
Benzene <sup>(1)</sup>	Ceiling Values - TWA PEL	25 ppm	
CAS: 71-43-2	8-hour TWA PEL	100 ppm	435 mg/m <sup>3</sup>
Ethylbenzene <sup>(1)</sup>	Ceiling Values - TWA PEL		
CAS: 100-41-4	8-hour TWA PEL	10 ppm	50 mg/m <sup>3</sup>
Naphthalene	Ceiling Values - TWA PEL		
CAS: 91-20-3			

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	20 ppm	
n-hexane	TLV-STEL		
CAS: 110-54-3	TLV-TWA	100 ppm	
cyclohexane			

(1) Skin

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-STEL		
CAS: 110-82-7	TLV-TWA	20 ppm	
Toluene <sup>(1)</sup>	TLV-STEL		
CAS: 108-88-3	TLV-TWA	0.5 ppm	
Benzene <sup>(1)</sup>	TLV-STEL	2.5 ppm	
CAS: 71-43-2	TLV-TWA	20 ppm	
Ethylbenzene <sup>(1)</sup>	TLV-STEL		
CAS: 100-41-4	TLV-TWA	10 ppm	
Naphthalene	TLV-STEL		
CAS: 91-20-3			

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
	PEL	50 ppm	180 mg/m <sup>3</sup>
n-hexane	STEL		
CAS: 110-54-3	PEL	300 ppm	1050 mg/m <sup>3</sup>
cyclohexane	STEL		
CAS: 110-82-7	PEL	10 ppm	37 mg/m <sup>3</sup>
Toluene <sup>(1)</sup>	STEL	150 ppm	560 mg/m <sup>3</sup>
CAS: 108-88-3	PEL	1 ppm	
Benzene <sup>(1)</sup>	STEL		
CAS: 71-43-2	PEL	5 ppm	22 mg/m <sup>3</sup>
Ethylbenzene <sup>(1)</sup>			



CAS: 100-41-4	STEL	30 ppm	130 mg/m <sup>3</sup>
Naphthalene	PEL	0.1 ppm	0.5 mg/m <sup>3</sup>
CAS: 91-20-3	STEL		

(1) Skin

### Biological limit values:


Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
n-hexane CAS: 110-54-3	0.5 mg/L	2,5-Hexanedione in urine	End of shift
cyclohexane CAS: 110-82-7	50 mg/g (NULL)	Cyclohexanol in urine	End of shift at end of workweek
Toluene CAS: 108-88-3	0.02 mg/L	Toluene in blood	Prior to last shift of workweek
Benzene CAS: 71-43-2	0.025 mg/g (NULL)	S-Phenylmercapturic acid in urine	End of shift
Ethylbenzene CAS: 100-41-4	150 mg/g (NULL)	Sum of mandelic acid and phenylglyoxylic acid in urine	End of shift
Naphthalene CAS: 91-20-3	0.0025 mg/L	1-Hydroxypyrene in urine	End of shift at end of workweek


## 8.2 Appropriate engineering controls:

- A. Individual protection measures, such as personal protective equipment  
Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection, ...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

### B. Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

### C. Specific protection for the hands


Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material cannot be calculated in advance with total reliability and has therefore to be checked prior to the application.


### D. Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)



### E. Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.



 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat-resistant properties	Replace boots at any sign of deterioration.
--	---	---

#### F. Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

##### Appearance:

Physical state at 20 °C (68 °F):	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Not available *

##### Volatility:

Boiling point at atmospheric pressure:	69 °C (157 °F)
Vapour pressure at 23 °C (74 °F):	18170 Pa
Vapour pressure at 50 °C (122 °F):	53182.53 Pa (53.18 kPa)
Evaporation rate at °C (74 °F):	Not available *

##### Product description:

Density at 23 °C (74 °F):	869.1 kg/m <sup>3</sup>
Relative density at 23 °C (74 °F):	0.869
Dynamic viscosity at 23 °C (74 °F):	Not available *
Kinematic viscosity at 23 °C (74 °F):	Not available *
Kinematic viscosity at 40 °C (104 °F):	<20.5 mm <sup>2</sup> /s
Concentration:	Not available *
pH:	Not available *
Vapour density at 23 °C (74 °F):	Not available*
Partition coefficient n-octanol/water 23 °C (74 °F):	Not available *
Solubility in water at 23 °C (74 °F):	Not available *
Solubility properties:	Not available *
Decomposition temperature:	Not available *
Melting point/freezing point:	Not available *

##### Flammability:

Flash Point:	-21.6 °C (-7 °F)
Flammability (solid, gas):	Not available *
Autoignition temperature:	234°C (453 °F)
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	
Median equivalent diameter:	Non-applicable

\*Not available due to the nature of the product, not providing information property of its hazards.

#### 9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not available *
Oxidising properties:	Not available *
Corrosive to metals:	Not available *
Heat of combustion:	Not available *
Aerosols-total percentage (by mass) of flammable	
Components:	Not available
Other safety characteristics:	Not available *
Surface tension at 23 °C (74 °F):	Not available *



Refraction index:

Not available \*

\*Not available due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

#### A. Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

#### B. Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### C. Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### D. CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Toluene (3); Benzene (1); Ethylbenzene (2B); Naphthalene (2B); Distillates (petroleum), hydrotreated light paraffinic,
- < 3 % IP 346 (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

#### E. Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

#### F. Specific target organ toxicity (STOT) - single exposure:





- Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G. Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H. Aspiration hazard:
  - May be fatal if swallowed and enters airways.

**Other information:**

Not applicable (N/A)

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
n-hexane CAS: 110-54-3	LD50 oral	>5000 mg/kg	Mouse
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Rosin CAS: 8050-09-7	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	212987.01 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available. Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**
**Acute toxicity:**

Identification	Concentration	Species	Genus
n-hexane CAS: 110-54-3	LC50 4 mg/L (96 h)	Carassius auratus	Fish
	EC50 Not applicable (N/A)		
	EC50 Not applicable (N/A)		
Rosin CAS: 8050-09-7	LC50 150 mg/L (96 h)	Brachydanio rerio	Fish
	EC50 238 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 185 mg/L (72 h)	Selenastrum capricornutum	Algae

**12.2 Persistence and degradability:**
**Substance-specific information:**

Identification	Degradability		Biodegradability	
n-hexane CAS: 110-54-3	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	Not applicable (N/A)	Period	14 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	100 %
Rosin CAS: 8050-09-7	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	32 %

**12.3 Bioaccumulative potential:**
**Substance-specific information**

Identification	Bioaccumulation potential	
n-hexane CAS: 110-54-3	BCF	542
	Pow Log	3.9
	Potential	High




**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
n-hexane CAS: 110-54-3	Koc	150	Henry	185425 Pa·m <sup>3</sup> /mol
	Conclusion	High	Dry soil	Yes
	Surface tension	1.798E-2 N/m (77 °F)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**
**13.1 Disposal methods:**

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Ignitability. The next EPA hazardous waste number could apply: D001.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

**SECTION 14: TRANSPORT INFORMATION**
**14.1 Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:



**UN number:** UN1133  
**UN proper shipping name:** ADHESIVES  
**Transport hazard class(es):** 3  
**Labels:** 3  
**Packing group, if applicable:** II  
**Marine pollutant:** Yes

**Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Physico-Chemical properties: see section 9

Limited quantities: 5 L

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**14.2 Transport of dangerous goods by sea:**

With regard to IMDG 41-22:



**UN number:** UN1133  
**UN proper shipping name:** ADHESIVES  
**Transport hazard class(es):** 3  
**Labels:** 3  
**Packing group, if applicable:** II  
**Marine pollutant:** Yes

**Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Special regulations: Not applicable (N/A)



EmS Codes:	F-E, S-D
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
Segregation group:	Not applicable (N/A)

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**14.3 Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



<b>UN number:</b>	UN1133
<b>UN proper shipping name:</b>	ADHESIVES
<b>Transport hazard class(es):</b>	3
<b>Labels:</b>	3
<b>Packing group, if applicable:</b>	II
<b>Marine pollutant:</b>	Yes

**Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Physico-Chemical properties: see section 9

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**SECTION 15: REGULATORY INFORMATION**

**15.1 HSR002662 Surface Coatings and Colourants (Flammable) Group Standard 2020.**

Refer to sections 11 and 12 in relation to the tolerable exposure limits (TEL) and environmental exposure limit (EEL).

**Safety, health and environmental regulations specific for the product in question:**

- CALIFORNIA LABOR CODE - *The Hazardous Substances List: n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3)*
- California Proposition 65 (*the Safe Drinking Water and Toxic Enforcement Act of 1986*) - *Birth defects or other reproductive harm: n-hexane (110-54-3); Toluene (108-88-3); Benzene (71-43-2)*
- California Proposition 65 (*the Safe Drinking Water and Toxic Enforcement Act of 1986*) - *Cancer: Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3)*
- CANADA-Domestic Substances List (DSL): *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7); Rosin (8050-09-7); Resin acids and Rosin acids, esters with pentaerythritol (8050-26-8); Distillates (petroleum), hydrotreated heavy paraffinic, < 3 % IP 346, < 20.5 cSt @ 40°C (64742-54-7); Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (64742-55-8)*
- CANADA-Non-Domestic Substances List (NDSL): *Not applicable (N/A)*
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - *Reportable Quantities: n-hexane (110-54-3) - 5000 lb; cyclohexane (110-82-7) - U056; Toluene (108-88-3) - U220; Benzene (71-43-2) - U019; Ethylbenzene (100-41-4) - 1000 lb; Naphthalene (91-20-3) - U165*
- Hazardous Air Pollutants (Clean Air Act): *n-hexane (110-54-3); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3)*
- Massachusetts RTK - *Substance List: n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7); Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (64742-55-8)*
- Minnesota - Hazardous substances ERTK: *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Rosin (8050-09-7)*
- New Jersey Worker and Community Right-to-Know Act: *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7)*
- New York RTK - *Substance list: n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7)*
- NTP (National Toxicology Program): *Benzene (71-43-2); Naphthalene (91-20-3)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): *Benzene (71-43-2)*
- Pennsylvania Worker and Community Right-to-Know Law: *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7)*
- Rhode Island - Hazardous substances RTK: *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3)*
- The Toxic Substances Control Act (TSCA) (USA, Puerto Rico): *n-hexane (110-54-3); cyclohexane (110-82-7); Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3); Methylcyclopentane (96-37-7); Rosin (8050-09-7); Resin acids and Rosin acids, esters with pentaerythritol (8050-26-8); Distillates (petroleum), hydrotreated heavy paraffinic, < 3 % IP 346, < 20.5 cSt @ 40°C*



- (64742-54-7); Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (64742-55-8)
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *n*-hexane (110-54-3); cyclohexane (110-82-7). Toluene (108-88-3); Benzene (71-43-2); Ethylbenzene (100-41-4); Naphthalene (91-20-3)

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

**Other legislation:**

Take into consideration other applicable federal, state, and local laws and local regulations.

**International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer – Not applicable

The Stockholm Convention on Persistent Organic Pollutants – Not applicable

The Rotterdam Convention – Not applicable

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets. It has been modified by Beacon Automation Ltd to meet New Zealand Hazardous Substances (Safety Data Sheets) Notice 2017 requirements under the Hazardous Substances and New Organisms Act 1996.

**Texts of the legislative phrases mentioned in section 2:**

H315: Causes skin irritation.

H361: Suspected of damaging fertility or the unborn child.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

H317: May cause an allergic skin reaction.

H304: May be fatal if swallowed and enters airways.

H225: Highly flammable liquid and vapour.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**29 CFR 1910.1200:**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Advice related to training:**

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 12/8/2023

Document generated with Chemeter [www.siam-it.com](http://www.siam-it.com)